Specialty Materials THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!

DecoFILM Paint FX

- Pearlescent transfer films that resemble the shimmer of car paint
- Pressure sensitive PET liner enables easy repositioning
- Adds considerable value that direct screen printing cannot reproduce
- Can be used on sport and leisure wear









Blue DFPX-5482

Champagne DFPX-5484

Pink DFPX-5485

Purple DFPX-5486

Application Instructions

Cotton, Uncoated Polyester, Fabric blends, Spandex, Lycra, Wool, Linen



45° Blade



Cut this material in mirror image



310°F - 330°F



Firm, even pressure.
Cover & reheat if necessary



17 - 20 seconds



Peel warm, then repress for 2 seconds



Wash inside out, cold water, gentle cycle. Dry low heat. Suitable for dry-cleaning.

No nylon.

★Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

★Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.